



TABELA DO WSTĘPNEGO USTALANIA WIELKOŚCI GWINTÓW

POMIAR GWINTU ZEWNĘTRZNEGO



POMIAR GWINTU WEWNĘTRZNEGO



Zewnętrzny	Wewnętrzny	Metryczny	BSP	UNF/ORFS	NPTF
9,3 - 9,7	8,5-8,9		1/8 - 28/cal		1/8" - 29/cal
9,7-9,9	8,2-8,6	M10x1,5			
10,9-11,1	9,7-10,0			7/16" - 20/cal	
11,6-11,9	10,2-10,6	M12x1,5			
12,4-12,7	11,3-11,6			1/2" - 20/cal	
12,9-13,1	11,4-11,9		1/4" - 19/cal		1/4 - 18/cal
13,6-13,9	12,2-12,6	M14x1,5			
14,0-14,3	12,7-13,0			9/16" - 18/cal	
15,6-15,9	14,2-14,6	M16x1,5			
16,3-16,6	14,9-15,4		3/8" - 19/cal		3/8" - 18/cal
17,1-17,4	15,8-16,1			11/16" - 16/cal	
17,6-17,9	16,2-16,6	M18x1,5			
18,7-19,0	17,3-17,6			3/4" - 16/cal	
19,6-19,9	18,2-18,6	M20x1,5			
20,3-20,6	18,9-19,3			13/16" - 15/cal	
20,5-20,9	18,6-19,0		1/2" - 14/cal		1/2 - 14/cal
21,6-21,9	20,2-20,6	M22x1,5			
22,0-22,2	20,2-20,5			7/8" - 14/cal	
22,6-22,9	20,6-21,0		5/8" - 14/cal		
23,6-23,9	22,2-22,6	M24x1,5			
25,1-25,4	23,4-23,8			1" - 14/cal	
25,6-25,9	24,2-24,6	M26x1,5			
26,1-26,4	24,1-24,5		3/4" - 14/cal		
26,6-26,9	24,3-24,7			1 1/16" - 12/cal	
26,6-26,9	24,6-25,0	M27x2			
26,6-26,9	25,2-25,6	M27x1,5			
29,6-29,9	27,4-27,8	M30x2			
29,8-30,1	27,6-27,9			1 3/16" - 12/cal	
29,6-29,9	28,2-28,6	M30x1,5			
33,0-33,2	30,3-30,8		1" - 11/cal		
32,6-32,9	30,6-31,0	M33x2			
32,6-32,9	31,2-31,6	M33x1,5			
33,0-33,3	30,8-31,2			1 5/16" - 12/cal	
32,9-33,4	30,3-30,8				1" - 11,5/cal
35,6-35,9	33,4-33,8	M36x2			
36,2-36,5	34,3-34,7			1 7/16" - 12/cal	
37,6-37,9	36,2-36,6	M38x1,5			
40,9-41,2	38,7-39,1			1 5/8" - 12/cal	
41,6-41,9	39,4-39,8	M42x2			
41,5-41,9	39,0-39,5		1 1/4" - 11/cal		
41,4-42,0	39,2-39,5				1 1/4" - 11,5/cal
42,5-42,8	40,6-41,0			1 11/16" - 16/cal	
44,6-44,9	42,4-42,8	M45x2			
47,3-47,6	45,1-45,5			1 7/8" - 12/cal	
47,4-47,8	44,8-45,3		1 1/2" - 11/cal		
47,3-47,9	45,1-45,5				1 1/2" - 11,5/cal
50,5-50,8	48,6-49,0			2" - 12/cal	
51,6-51,9	49,4-49,6	M52x2			
59,2-59,6	56,2-56,6		2" - 11/cal		